	CENTRA	N GERGEAGE N. INTERLIGENCE AGE	NEY surgeon see	2
		WATION REP	and the section	
	iiii Oni	MATION REP	CD NO.	
COUNTRY	East Germany	•	DATE DISTR.	17 April 1953
SUBJECT	Radar Training of the	e 1st Volkspolizei	NO. OF PAGES	
	Air Division 25X1C			2
		•	NO. OF ENCLS.	
			SUPPLEMENT 1	το
			REPORT NO.	
		25X1X		
	4			
		miched by the Russ'	e of which could not be	•
2. T	he effectiveness of the	redar set is depend aircraft, as well	dent on the number, typ as to the position of a	e, alti-
2. T	•	related by the Russ: redar set is dependent aircraft, as well a following data were	dent on the number, typ as to the position of a given:	e, alti-
2. T t	he effectiveness of the	related by the Russ: redar set is dependent aircraft, as well a following data were	dent on the number, typ as to the position of a	e, alti-
2. T t	he effectiveness of the ude and distance of the nd radar station. The intitude of Aircraft 2,000 meters	related by the Russ: redar set is dependent aircraft, as well a following data were	dent on the number, typ as to the position of a given: Range of Radar 65 kilometers	e, alti-
2. T t	he effectiveness of the ude and distance of the nd radar station. The intitude of Aircraft 2,000 meters 4,000 meters	related by the Russ: redar set is dependent aircraft, as well a following data were	dent on the number, typ as to the position of a given: Range of Radar	e, alti-
2. T t	he effectiveness of the ude and distance of the nd radar station. The intitude of Aircraft 2,000 meters	related by the Russ: redar set is dependent aircraft, as well a following data were	dent on the number, typ as to the position of a given: Range of Radar 65 kilometers 100 kilometers	e, alti-
2. T t a	he effectiveness of the ude and distance of the nd radar station. The intitude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters	rnished by the Russ: redar set is dependent aircraft, as well a following data were	dent on the number, typ as to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilometers	e, alti- ircraft
2. Tt a	he effectiveness of the ude and distance of the nd radar station. The intitude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters 8,000 meters enterfere with the relaymeters.	rnished by the Russ: redar set is dependent aircraft, as well a following data were t has to be cleared a (radiation) of the	dent on the number, type as to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilometers 150 kilometers if rom all obstacles which waves, at a redius of	e, alti- ircraft ich might 500 to 600
2. Tta	the effectiveness of the sude and distance of the sude and distance of the sude and radar station. The substitute of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters The area of the radar sessinterfere with the relaymeters. The average error in mean total relaymeters.	redar set is dependent aircraft, as well a following data were the these to be cleared a (radiation) of the surement at an azimarings to altitudes	dent on the number, typ as to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilometers 150 kilometers with angle of 2 degrees	e, alti- ircraft ich might 500 to 600 amounts e error in
2. Tta	he effectiveness of the ude and distance of the nd radar station. The i lititude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters Ene area of the radar se interfere with the relay meters. The average error in mea to 700 meters. Taking be measurement is	redar set is dependent aircraft, as well a following data were the these to be cleared a (radiation) of the surement at an azimarings to altitudes	dent on the number, type as to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilometers 150 kilometers while waves, at a redius of the second of the secon	e, alti- ircraft ich might 500 to 600 amounts e error in
2. Tta	he effectiveness of the ude and distance of the nd radar station. The i lititude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters 8,000 meters The area of the radar se interfere with the relay meters. The average error in mea 7,700 meters. Taking be measurement is immeters = 500 meters.	redar set is dependent aircraft, as well a following data were the these to be cleared a (radiation) of the surement at an azimarings to altitudes	dent on the number, type as to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilometers 150 kilometers while waves, at a redius of the second of the secon	e, alti- ircraft ich might 500 to 600 amounts e error in
2. Tta	the effectiveness of the sude and distance of the sude and distance of the sude and radar station. The substitute of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters 8,000 meters The area of the radar sestinterfere with the relaymeters. The average error in mea measurement is meters = 500 meters. Technical data: a. Transmitter.	redar set is dependent aircraft, as well a following data were the these to be cleared a (radiation) of the surement at an azimarings to altitudes 300 meters, and to	dent on the number, types to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilometers 150 kilometers 150 kilometers 150 kilometers 150 kilometers 150 kilometers 151 characters 152 kilometers 153 kilometers 154 kilometers 155 kilometers 155 kilometers 156 kilometers 157 kilometers 157 kilometers 158 kilometers 159 kilometers 150 kilomet	e, alti- ircraft ich might 500 to 600 amounts e error in 00 and 8,000
2. Tta	the effectiveness of the sude and distance of the sude and distance of the sude and radar station. The substitute of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters 8,000 meters The area of the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters.	redar set is dependent aircraft, as well a following data were the these to be cleared a (radiation) of the surement at an azimarings to altitudes 300 meters, and to	dent on the number, types to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilomet	e, alti- ircraft ich might 500 to 600 amounts e error in 00 and 8,000
2. Tta	the effectiveness of the sude and distance of the sude and distance of the sude and radar station. The substitute of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters 8,000 meters The area of the radar sestinterfere with the relaymeters. The average error in mean means are 700 meters. Taking be measurement is the meters - 500 meters. Technical data: a. Transmitter. Operating frequency Impulse frequency Impulse frequency Inpulse period	redar set is dependent aircraft, as well a following data were the state of the cleared a (radiation) of the surement at an azimarings to altitudes 300 meters, and to	dent on the number, types to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilometers 150 kilometers 150 kilometers 150 kilometers 150 kilometers 150 kilometers 151 characters 152 kilometers 153 kilometers 154 kilometers 155 kilometers 155 kilometers 156 kilometers 157 kilometers 157 kilometers 158 kilometers 159 kilometers 150 kilomet	e, alti- ircraft ich might 500 to 600 amounts e error in 00 and 8,000
2. Tta	the effectiveness of the sude and distance of the sude and distance of the sude and radar station. The substitute of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters 8,000 meters The area of the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters. The average error in mea to the radar sestinterfere with the relaymeters.	redar set is dependent aircraft, as well a following data were the state of the cleared a (radiation) of the surement at an azimarings to altitudes 300 meters, and to	dent on the number, types to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilomet	e, alti- ircraft ich might 500 to 600 amounts e error in 00 and 8,000
2. Tta	the effectiveness of the sude and distance of the sude and distance of the sude and radar station. The substitute of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters 8,000 meters The area of the radar sestinterfere with the relaymeters. The average error in means to measurement is to measurement is to meters. Technical data: a. Transmitter. Operating frequency Impulse frequency Impulse frequency Inpulse period Average cathode outs	redar set is dependent aircraft, as well a following data were the state of the cleared a (radiation) of the surement at an azimarings to altitudes 300 meters, and to	dent on the number, types to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilomet	e, alti- ircraft ich might 500 to 600 amounts e error in 00 and 8,000
2. Tta	the effectiveness of the sude and distance of the sude and distance of the sude and redar station. The substitute of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters The area of the radar sest set of the radar sest sest sest sest sest sest sest ses	redar set is dependent aircraft, as well a following data were the state of the cleared at a state of the surement at an azimarings to altitudes 300 meters, and to the surement at an azimarings to altitudes and the surement at an azimarings and the surement at a surement	dent on the number, types to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilomet	e, alti- ircraft ich might 500 to 600 amounts e error in 00 and 8,000
2. Tta	the effectiveness of the sude and distance of the sude and distance of the sude and radar station. The substitute of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters 8,000 meters The area of the radar sestinterfere with the relaymeters. The average error in means to measurement is to measurement is to meters. Technical data: a. Transmitter. Operating frequency Impulse frequency Impulse frequency Inpulse period Average cathode outs	redar set is dependent aircraft, as well a following data were the state of the cleared at a state of the surement at an azimarings to altitudes 300 meters, and to the surement at an azimarings to altitudes and the surement at an azimarings and the surement at a surement	dent on the number, types to the position of a given: Range of Radar 65 kilometers 100 kilometers 120 kilometers 150 kilomet	e, alti- ircraft ich might 500 to 600 amounts e error in 00 and 8,000

S	ECRET/	25X1	25X1A
be	Receiver.		
De-	Frequency range first interrediate frequency second intermediate frequency	110 to 160 kilocycles 5.95 to 6.05 megacycles 1.65 to 1.75 megacycles	
C.	Power supply Alternating current	50 cycles, 220 volts	

- 6. Operation. During summer months, four hours are required to erect the radar set, and during the winter months, six hours are required for the procedure. The set is ready for operation 3 to 5 minutes after it has been turned on. The starting time of the generator is three minutes in summer and 5 to 8 minutes in winter. Fuel consumption of the generator: 335 gramms gasoline and 17 gramms oil per hp per hour. After six hours of continuous operation, a second generator has to be turned on.
 - 1. Correct. It is believed that the data given refer to the approximate figures of the Fumbo or SCR-602 radar sets. The average error in measurement is probably to high, while the frequency range of the receiver is believed to be too small. The training was performed in connection with early warning stations.

25X1A

escret/	1×	25X1